Model	Go-Go® Ultra X ¹
Part Number	3-wheel: S39 4-wheel: S49
Weight Capacity	300 lbs.
Maximum Speed ²	3-wheel: Up to 4.3 mph 4-wheel: Up to 4.1 mph
Ground Clearance ⁴	1.25" at motor 3.23" at deck
Turning Radius ⁴	3-wheel: 36.5" 4-wheel: 52.25"
Overall Length ⁴	40.25"
Overall Width ⁴	19.25"
Seat-to-Deck Height	16.5 - 18"
Seat-to-Ground Height	21.5 - 23"
Tires	Front: 2"x 8" Rear: 2.5"x 8"
Range Per Charge ^{2,3}	3-wheel: Up to 8 miles (200 lbs.) 3-wheel: Up to 6.2 miles (300 lbs.) 4-wheel: Up to 8.9 miles (200 lbs.) 4-wheel: Up to 6.6 miles (300 lbs.)
Total Weight With Batteries	3-wheel: 95.75 lbs. 4-wheel: 101 lbs.
Total Weight Without Batteries	3-wheel: 76.25 lbs. 4-wheel: 81.5 lbs.
Heaviest Piece When Disassembled ⁴	3-wheel: 29.5 lbs. (front section) 4-wheel: 34.5 lbs. (front section)
Standard Seating	Type: Compact, foldable Weight: 23 lbs. Material: Black vinyl Dimensions: 17"x17"
Motor Output	24-volt DC motor, sealed transaxle
Brakes	Regenerative and electromechanical
Battery Requirements ⁵	(Two) 12 AH Weight: 9 lbs. each
Battery Charger	Off-board, 2 amp
Warranty	Lifetime limited on frame 2-year limited on electronics 2-year limited on drivetrain

HCPCS Code: K0899

POWER MOBILITY DEVICE, NOT CODED BY DME PDAC OR DOES NOT MEET CRITERIA

- 1 Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.
- 2 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
- 3 Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight
- 4 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- 5 Battery weight may vary based on manufacturer.



(US) 800-800-8586 • (Canada) 888-570-1113

pridemobility.com | • • • • • •





HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3 %. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.





The Go-Go® Ultra X is loaded with features such as one-hand disassembly and a convenient dropin battery box for worry-free travel. With a 300 lb. weight capacity and impressive speed and range, the Go-Go Ultra X is an exceptional value.

Additional Features

- 17"x17" compact foldable seat with new mesh back
- Easy-to-grip tiller adjustment knob
- Standard front basket
- Feather-touch disassembly easily disassembles into 5 lightweight pieces for transport and storage
- Charger port conveniently located on tiller to charge your scooter
- Dual voltage charger permits charging the battery pack on-board or off-board for added convenience
- Pride's exclusive black, non-scuffing tires
- HCPCS Code: K0899 power mobility device, not coded by DME PDAC or does not meet criteria

Shroud Color

Black

Accessories*

- 12 Ah battery box
- 2.1A XLR USB charger
- Cup holder
- Forearm crutch holder
- Oxygen holder
- Rear basket
- Rear mount 3" double cane/crutch holder
- Saddle bag
- Safety flag
- Single rear mount 3" cane/crutch holder
- Under seat storage
- Walker holder
- Weather cover
- Wishbone crutch holder

Military Patches



* Only one rear accessory can be used at a time.