Express Dumbwaiter EVALUATION/ORDER FORM

Date			Account Number			
Sales Representative			Projected Close Date			
Name			Purchase Order Number			
			Ship To Address	<u> </u>		
	StateZip					
	Fax					
Email			Contact			
□ Quote □ Order			Phone Residential - Single Family Home			
			Application:	☐ Resident	iai - Single Family Home	
Shipping Method:			Is there an occu	pied space belov	v hoistwav?	
☐ Pick-up ☐ Common Carrier			☐ Yes ☐ No			
Flatbed w/Forklift ☐ Yes ☐ No			Opportunity Reference / Project Name			
Car Configuration	n (Please Check One):					
	(- 101100 0110011 0110)					
_						
_	_					
_	_					
STD	STD	STD	DW005	DW090	DW090	
				(Requires EMI D	NW(008)	
N 1 (6)			Cor Ci-or	(Nequires EMI D	, (video)	
Number of Stops	:		Car Size:			
☐ Standard 2 Sto	р		☐ Standard 20"W x 20"D x 30"H w/ 100 lbs. capacity			
☐ DW020 3 Stop			☐ DW024 24"W x 24"D x 30"H w/ 150 lbs. capacity			
☐ DW025 4 Stop			<u> </u>			
Capacity			☐ DW035 Custom Size Car			
☐ Standard 100 lb	26					
☐ DW150 150 lbs.			Car size determines capacity requirements			
_ DW130 130 lb3.			Width (Min. 16" - Max. 24")			
			Depth (Min. 16" - Max. 24")			
True of Interlock			Height	(30")		
Type of Interlock	5.		Stainless stee	el - #3 finish		
G.A.L. (Std)	(Req. with 90° cars) resider	atial usa	_			
only.	(neq. with 90 cars) resider	itiai use	☐ DW100 SS 20 x 20 x 30			
☐ Commerical inte	erlock		☐ DW024 SS 24 x 24 x 30			
CPL008L EMI (H	-		☐ DW035 SS Custom Car Size			
CPL008R EMI (H	•		_ D V V O J J J J J J	Castorii Car 3120		
☐ No Interlocks - v	wired for EMI					
Brand	istanal Landin Coord					
	itional Landing Opening Call/Send & Wiring)					

Unfinished Maple Hoistway Doors: Optional Equipment: ☐ DW010 Intermediate Car Shelf DW050 Landing Door - Matches Car Opening ☐ CPL026 Float Level Switch ☐ DW055 Machine Access Door - 18" x 24" ☐ DW015 Keylocks on Call/Send (each) ☐ DW044 In Car Light DW045 "Car Here" Indicator _____Qty. ☐ DW060 Remote Mount Controller Package ☐ DW065 Floor Mount Drive Unit (Includes RMC) ☐ DW070 Automatic Homing ☐ DW080 Access Door (Kill Switch) Hoistway Layout - Provide architectural plans if available **Travel Measurements Hoistway Door Locations** 1st Floor to 2nd Floor Track 2nd Floor to 3rd Floor ☐ 1st Floor ☐ 1st Floor 3rd Floor to 4th Floor ___ □ 2nd Floor □ 2nd Floor Top Floor to Ceiling ☐ 3rd Floor ☐ 3rd Floor Travel up to 12' - 0" (No Charge) ☐ 4th Floor ☐ 4th Floor ☐ 1st Floor □ DW018 12' - 1" to 18' - 0" ☐ 2nd Floor □ DW026 18' - 1" to 26' - 0" ☐ 3rd Floor DW032 26' - 1" to 32' - 0" ☐ 4th Floor **Hoistway Door Swings Top Floor** to Ceiling **Right Hand Swing Left Hand Swing** ☐ 1st Floor ☐ 1st Floor ☐ 2nd Floor □ 2nd Floor ☐ 3rd Floor ☐ 3rd Floor ☐ 4th Floor ☐ 4th Floor Width Floor Typical Sill to Floor **Existing Hoistway** Track Height is 36" Width Depth

An application drawing will be emailed for approval before production will begin.

Drawings
□ DRAWING FOR APPROVAL An application-specific drawing is requested and production will be scheduled after return of signed approval drawing Upcharge if lift is not ordered within 90 days of drawing submission.
ADDITIONAL INFORMATION
VISIBLE DAMAGE: You must note any visible damage on the freight bill. If product damage is obvious, we recommer a further immediate inspection to see what other damage may be concealed, and this also must be written on the freight bill.
CONCEALED DAMAGE: If no damage was immediately evident, but is found later (within 48 hours), stop what you a doing and call the freight company immediately to report concealed damage.
Pictures of the damage are great support in any freight claim and are strongly recommended. Failure to take these ste may preclude your ability to be reimbursed for any damage in transit. We have personnel available to assist with the process Monday – Friday, 7:30 am – 5:00 pm CST by calling 800-833-0478.
Thank you for your business
AmeriGlide Accessibility Solutions
I have read and understand the above:
Date:
Print Name:
SIgn Name: